

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

| | | |
|---|-----------|---|
| (51) International Patent Classification 6 : B32B 27/06, A61L 15/42, 15/22 | A1 | (11) International Publication Number: WO 99/64237 (43) International Publication Date: 16 December 1999 (16.12.99) |
| (21) International Application Number: PCT/IB99/00978 (22) International Filing Date: 1 June 1999 (01.06.99) (30) Priority Data: 98110593.5 9 June 1998 (09.06.98) EP (71) Applicant (for all designated States except US): THE PROCTER & GAMBLE COMPANY [US/US]; One Procter & Gamble Plaza, Cincinnati, OH 45202 (US). (72) Inventors; and (75) Inventors/Applicants (for US only): PALUMBO, Gianfranco [IT/DE]; Georgenfeld 7, D-61348 Bad Homburg (DE). CORZANI, Italo [IT/IT]; Via Fontevicchia, 40, I-66100 Chieti (IT). (74) Agents: REED, T., David et al.; The Procter & Gamble Company, 5299 Spring Grove Avenue, Cincinnati, OH 45217-1087 (US). | | (81) Designated States: AE, AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> |

(54) Title: MOISTURE VAPOUR PERMEABLE COMPOSITE STRUCTURE AND THE UTILISATION THEREOF IN ABSORBENT ARTICLES**(57) Abstract**

The present invention relates to liquid impermeable moisture vapour permeable composite structures comprising a specific thermoplastic film which is coated onto a support layer. The composite structures of the present invention can find a variety of applications wherein moisture vapour permeability is desirable, such as within absorbent articles for example diapers, sanitary napkins, panty liners and incontinence products, and also protective bedding covers, protective clothing and the like.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

| | | | | | | | |
|----|--------------------------|----|--|----|--|----|--------------------------|
| AL | Albania | ES | Spain | LS | Lesotho | SI | Slovenia |
| AM | Armenia | FI | Finland | LT | Lithuania | SK | Slovakia |
| AT | Austria | FR | France | LU | Luxembourg | SN | Senegal |
| AU | Australia | GA | Gabon | LV | Larvia | SZ | Swaziland |
| AZ | Azerbaijan | GB | United Kingdom | MC | Monaco | TD | Chad |
| BA | Bosnia and Herzegovina | GE | Georgia | MD | Republic of Moldova | TG | Togo |
| BB | Barbados | GH | Ghana | MG | Madagascar | TJ | Tajikistan |
| BE | Belgium | GN | Guinea | MK | The former Yugoslav Republic of Macedonia | TM | Turkmenistan |
| BF | Burkina Faso | GR | Greece | ML | Mali | TR | Turkey |
| BG | Bulgaria | HU | Hungary | MN | Mongolia | TT | Trinidad and Tobago |
| BJ | Benin | IE | Ireland | MR | Mauritania | UA | Ukraine |
| BR | Brazil | IL | Israel | MW | Malawi | UG | Uganda |
| BY | Belarus | IS | Iceland | MX | Mexico | US | United States of America |
| CA | Canada | IT | Italy | NE | Niger | UZ | Uzbekistan |
| CF | Central African Republic | JP | Japan | NL | Netherlands | VN | Viet Nam |
| CG | Congo | KE | Kenya | NO | Norway | YU | Yugoslavia |
| CH | Switzerland | KG | Kyrgyzstan | NZ | New Zealand | ZW | Zimbabwe |
| CI | Côte d'Ivoire | KP | Democratic People's Republic of Korea | PL | Poland | | |
| CM | Cameroon | KR | Republic of Korea | PT | Portugal | | |
| CN | China | KZ | Kazakstan | RO | Romania | | |
| CU | Cuba | LC | Saint Lucia | RU | Russian Federation | | |
| CZ | Czech Republic | LI | Liechtenstein | SD | Sudan | | |
| DE | Germany | LK | Sri Lanka | SE | Sweden | | |
| DK | Denmark | LR | Liberia | SG | Singapore | | |
| EE | Estonia | | | | | | |

MOISTURE VAPOUR PERMEABLE COMPOSITE STRUCTURE AND THE UTILISATION THEREOF IN ABSORBENT ARTICLES

Field of the Invention

The present invention relates to liquid impermeable moisture vapour permeable composite structures comprising a specific thermoplastic film which is thinly coated onto a support layer. The composite structures of the present invention can find a variety of applications, wherein moisture vapour permeability is desirable for example within absorbent articles such as diapers, sanitary napkins, panty liners and incontinence products, protective bedding covers, protective clothing and the like.

Background of the Invention

Thermoplastic films which provide a liquid barrier in addition to providing moisture vapour permeability are known in the art. Particularly preferred are hydrophilic continuous films that do not allow the flow of moisture vapour through open pores or apertures in the material, but do transfer substantial amounts of moisture vapour through the film by absorbing water on one side of the film where the moisture vapour concentration is higher, and desorbing or evaporating it on the opposite side of the film where the moisture vapour concentration is lower. Compositions used to form hydrophilic continuous, moisture vapour permeable, liquid impervious films are also said to be moisture vapour permeable, liquid impervious.

For example WO 95/16746 discloses films prepared from mixtures of a) block copolyether ester, block copolyether amides (e.g. Pebax™) and or polyurethane and b) thermoplastic polymer which is incompatible with a, and c) a compatibiliser. The films are liquid impermeable and have moisture vapour permeability of about 700g/m²/day. Also, US 5 447 783 discloses a vapour permeable water resistant multi component film structure having at least three

layers. The outer layers are hydrophobic copolyetherester elastomers having a thickness of 1.3-7.6 micrometers and a WVTR of 400-2500 g/m²/24hrs. and the inner layer is a hydrophilic copolyetherester elastomer having a thickness of 7.6-152 micrometers and a WVTR of at least 3500 g/m²/24hrs.

US 5 445 875 discloses a waterproof, bloodproof and virusproof breathable laminate. The laminate comprises a woven/nonwoven fabric and an extruded film such as Hytrel™ having a thickness of about 1mil.

However, whilst these films are desirable in so far as their moisture vapour transport rate is concerned, these films tend to lack other desirable physical characteristics such as tear strength and flexibility depending on the end usage envisioned.

Attempts to address this problem have resided in providing the polymers on a supportive substrate which provides the required physical attributes. Such composites are described for example in US 5 599 610 which discloses tri-laminated fabric for surgical gowns comprising outer layers of woven fabric and an inner layer of a microporous polyurethane membrane. The microporous film has a thickness of 12-55 micrometers and a MVTR of 1100 g/m²/24hrs. upright and 5500 g/m²/24hrs. inverted (ASTM E96-B). Polyether-polyurethane adhesive is used to join the layers.

Similarly, US 5 532 053 discloses a high moisture transmission medical film which can be laminated onto a nonwoven material. The laminate film comprises a first layer of polyetherester copolymer and second and third layers selected from a specified group of polymers. The film has a MVTR of greater than 750 g/m²/24hrs. (ASTM F1249) and a thickness of less than 1mil (25.4micrometer) preferably 0.6mm to 0.75mm (15-19 micrometers).

US 4 938 752 discloses absorbent articles comprising films of copolyether esters which have reduced water permeability, a water vapour permeability of 500g/m²/24hrs. (as measured in a specified described test) and a thickness of 5-35micrometers. There is no disclosure of a supportive substrate.

US 4 493 870 discloses a flexible layered waterproof product comprising a textile material covered with a film of a copolyetherester having an MVTR of at least $1000 \text{ g/m}^2/24\text{hrs.}$ (ASTM E96- 66) having a thickness of 5 to 35 micrometers.

GB 2 024 100 discloses a flexible layered water resistant article comprising a microporous hydrophobic outer layer which is moisture vapour permeable but resist liquids and a hydrophilic inner layer of polyetherpolyurethane having a MVTR of above $1000\text{g/m}^2/24\text{hrs.}$

However a problem with the films disclosed in the prior art is that the thickness at which the films can be readily extruded onto a support substrate is severely limited using standard extrusion techniques. Furthermore such films often require the addition of an adhesive in order to ensure permanent fixation of the coating to the substrate. However, this in turn detrimentally affects the overall moisture vapour permeability of the resulting composite.

Hence, there is a need to provide a composite structure which is liquid impermeable and moisture vapour permeable and which is readily processable so as to provide a thin film coating.

Summary of the Invention

The present invention relates to a moisture vapour permeable liquid impervious composite substrate.

Said substrate comprises:

(a) a thermoplastic film made from a moisture vapour permeable thermoplastic composition having a complex viscosity of from 50 poise to 4000 poise at a frequency of 1rad/s , at a temperature of 210°C or less, and a complex viscosity of less than 2000 poise at a frequency of 1000rad/s and at a temperature of 210°C or less, said film having a thickness of less than 10 micrometers to 0.5 micrometers and

(b) a support layer, said support layer being moisture vapour permeable.

The thermoplastic compositions from which the polymeric films of the present invention are made may in addition comprise additional optional components to further improve the processibility of the film and mechanical characteristics as well as other characteristics as its tackiness, its resistance to ageing by light and oxygen, its visual appearance etc.

Such optional components include tackifying resins or blends of tackifying resins having a softening point of 125°C or less. Preferred resins, which may be present by up to 50% by weight, may be selected from rosins and rosin esters, hydrocarbon resins, aliphatic resins, terpene and terpene-phenolic resins, aromatic resins, synthetic C₅ resins, mixtures of synthetic C₅-C₉ resins, and mixtures thereof. Other optional components of said thermoplastic composition include anti-oxidants, anti-ultraviolet, pigments and mixtures thereof, which may be present within the film at a level of up to 10% by weight of the thermoplastic composition.

The films of the present invention also preferably have a moisture vapour transport rate of at least 100 g/(m². 24 hours), preferably at least 300 g/(m². 24 hours), most preferably at least 500 g/(m². 24 hours).

According to the present invention the composite structure further comprises as an essential element a support layer upon which the thermoplastic layer is typically directly coated. The support layer may be any useful layer provided that it is moisture vapour permeable, preferably having a moisture vapour permeability of at least 100 g/(m². 24 hours), more preferably at least 300 g/(m². 24 hours), and most preferably at least 500 g/(m². 24 hours).

Suitable support layers for use herein include 2 dimensional, planar micro and macro-porous films; macroscopically expanded films; formed apertured films; nonwoven and woven layers. According to the present invention the apertures in said layer may be of any configuration, but are preferably spherical or oblong and may also be of varying dimensions. The apertures preferably are evenly distributed across the entire surface of the layer, however layers having only certain regions of the surface having apertures are also envisioned.

Suitable 2 dimensional porous planar layers of the backsheet may be made of any material known in the art, but are preferably manufactured from commonly available polymeric materials. Suitable materials are for example Goretex (TM) or Sympatex (TM) type materials well known in the art for their application in so-called breathable clothing. Other suitable materials include XMP-1001 of Minnesota Mining and Manufacturing Company, St. Paul, Minnesota, USA and Exxair XBF-101W, supplied by the Exxon Chemical Company. As used herein the term 2 dimensional planar layer refers to layers having a depth of less than 1mm, preferably less than 0.5mm, wherein the apertures have an average uniform diameter along their length and which do not protrude out of the plane of the layer. The apertured materials for use as a backsheet in the present invention may be produced using any of the methods known in the art such as described in EPO 293 482 and the references therein. In addition the dimensions of the apertures produced by this method may be increased by applying a force across the plane of the backsheet layer (i.e. stretching the layer).

Suitable apertured formed films include films which have discrete apertures which extend beyond the horizontal plane of the garment facing surface of the layer towards the core thereby forming protuberances. The protuberances have an orifice located at its terminating end. Preferably said protuberances are of a funnel shape, similar to those described in US 3, 929,135. The apertures located within the plane and the orifices located at the terminating end of protuberance themselves maybe circular or non circular provided the cross sectional dimension or area of the orifice at the termination of the protuberance is smaller than the cross sectional dimension or area of the aperture located within the garment facing surface of the layer. Preferably said apertured performed films are uni directional such that they have at least substantially, if not complete one directional fluid transport towards the core.

Suitable macroscopically expanded films for use herein include films as described in for example in US 4 637 819 and US 4 591 523.

Preferred support layers for use herein include woven and nonwoven layers, most preferably hydrophobic fibrous layers such as hydrophobic non woven.

The composites of the present invention are particularly advantageous as they allow the possibility of providing a composite wherein the thermoplastic composition may be coated onto the support substrate as a film with the desired thickness. This is in contrast to current films which can only be extruded or coated onto the substrate relatively thickly. Typical coating conditions and apparatuses known in the art for the direct coating of low viscosities hot melts can be readily utilised in order to provide the thermoplastic composition at the required thickness.

A possible method for forming a composite laminate by coating the thermoplastic composition onto a substrate acting as a support layer is described in PCT application WO 96/25902.

At least at the coating temperature, the thermoplastic composition of the film preferably exhibits adhesive properties on the supportive layer such that no additional adhesive is required to achieve a permanent attachment between the film and the layer. In some applications it may be also desirable that the polymeric film remains tacky at any temperature i.e. it is formulated so to have the typical characteristics of a pressure sensitive adhesive.

The composite structures of the present invention find utility in a number of applications wherein liquid imperviousness and moisture vapour permeability are desirable. In particular the present invention can be effectively utilised within absorbent articles such as diapers, sanitary napkins, panty liners and incontinence products; perspiration pads such as underarm-, wrist- and head perspiration pads, collar inserts, shoe inserts, hat bands and breast pads; protective bedding covers, protective clothing and the like. Preferably the composite structures of the present invention have a moisture vapour transfer rate of at least 100 g/(m². 24 hours), more preferably at least 300 g/(m². 24 hours), and most preferably at least 500 g/(m². 24 hours).

The composite structure of the present invention find particular utility as the backsheet for absorbent articles especially sanitary napkins and panty liners. Such articles will typically comprise components known to the skilled

person such as a liquid pervious topsheet, an absorbent core and backsheet and may optionally comprise fastening means, wings, and the like.

Example:

A polyether based thermoplastic polyurethane available from BF Goodrich Co.-USA commercialised under the trade name Estane 58245 was compounded with triethyl citrate available from Aldrich Co. and Irganox 1010 (anti oxidant agent) available from Ciba-Geigy.

The final formulation in percent by weight had the following composition:

| | |
|-----|------------------|
| 30% | Estane 58245 |
| 69% | Triethyl Citrate |
| 1% | Irganox 1010 |

The blend was melt coated at 175°C to obtain a film having a thickness equal to 5µm. At the coating temperature it was found to have complex viscosities of 370 poise and 27 poise respectively at 1 and 1000 rad/s shear rate. The film was then laminated directly onto a 100% polyester spunlaced nonwoven 40 g/m² (support layer) commercialised under the trade name Fibrella 4100, available from Suominen (Finland). The composite substrate had a moisture vapour transfer rate of 1140 g/m².24hrs.

According to the present invention the complex viscosity is measured using a Rheometer RDA-II available from Rheometrics Co. Water vapour permeability is measured at 23°C according to the ASTM E-96 "Upright Cup" method.

WHAT IS CLAIMED IS:

1. A moisture vapour permeable liquid impervious composite substrate comprising;
 - (a) a thermoplastic film made from a moisture vapour permeable thermoplastic composition, said composition having a viscosity of from 50 poise to 4000 poise at a frequency of 1rad/s at a temperature of 210°C or less and a frequency of less than 2000 poise at a viscosity of 1000rad/s at a temperature of 210°C or less and said film having a thickness of from less than 10 micrometers to 0.5 micrometers and
 - (b) a support layer said layer being moisture vapour permeable.
2. A moisture vapour permeable composite substrate according to claim 1, wherein said thermoplastic film comprises from 5% to 100% by weight of a polymer or mixture of polymers.
3. A moisture vapour permeable liquid impervious composite substrate according to claim 2, wherein said polymers are selected from polyurethanes, poly-ether-amides block copolymers, polyester block copolymers, and poly-ether-ester-amide block copolymers and mixtures thereof.
4. A moisture vapour permeable liquid impervious composite substrate according to claim 1, wherein said film further comprises from 20% to 90% by weight of a plasticiser.
5. A moisture vapour permeable liquid impervious composite substrate according to claim 1, wherein said plasticisers are selected from citric acid esters and tartaric acid esters and mixtures thereof.
6. A moisture vapour permeable liquid impervious composite substrate according to claim 1, wherein said temperature from 200°C to 50°C.

7. A moisture vapour permeable liquid impervious composite substrate according to claim 1, wherein said composite substrate has a water vapour transfer rate of at least $300\text{g}/(\text{m}^2 \cdot 24\text{hrs.})$.
8. A moisture vapour permeable liquid impervious composite substrate according to claim 1, wherein said film has a thickness of from 9 micrometers to 0.5 micrometers, preferably from 8 micrometers to 2 micrometers.
9. A moisture vapour permeable liquid impervious composite substrate according to claim 1, wherein said support layer is selected from wovens, nonwovens and apertured films.
10. An absorbent article comprising said composite substrate according to any one of the preceding claims.

INTERNATIONAL SEARCH REPORT

Int. Application No.

PCT/IB 99/00978

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 B32B27/06 A61L15/42 A61L15/22

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 A61L C08K B32B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

| Category * | Citation of document, with indication, where appropriate, of the relevant passages | Relevant to claim No. |
|------------|--|-----------------------|
| X | WO 96 25902 A (FULLER H B GMBH ; WERENICZ HARALD (DE); WITTKOPF THOMAS (DE); VOSS) 29 August 1996 (1996-08-29) page 1, line 21 - line 35 page 4, line 16 - page 5, line 10 page 8, line 20 - line 24 page 8, line 31 - page 9, line 1 page 10, line 10 - line 31 claims; table 1 --- | 1-10 |
| X | EP 0 295 694 A (TOPPAN PRINTING CO LTD) 21 December 1988 (1988-12-21) claims; tables 3,10 --- -/-- | 1-3,6-9 |



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

7 September 1999

Date of mailing of the international search report

17/09/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl.

Authorized officer

Gouda - Van Staan G

INTERNATIONAL SEARCH REPORT

International Application No

PLT/IB 99/00978

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

| Category * | Citation of document, with indication, where appropriate, of the relevant passages | Relevant to claim No. |
|------------|--|-----------------------|
| A | <p>US 4 758 239 A (SCHIFFER DANIEL K ET AL) 19 July 1988 (1988-07-19) column 1, line 34 - line 58 column 9, line 35 - line 51 column 12, line 60 - column 15, line 6 claims; examples</p> <p>----</p> | 1-10 |
| A | <p>EP 0 539 604 A (NIPPON SYNTHETIC CHEM IND) 5 May 1993 (1993-05-05) page 4, line 16 - line 26 page 6, line 10 - line 42 page 7, line 15 - page 8, line 5 claims; examples</p> <p>----</p> | 1-10 |
| A | <p>GB 1 341 605 A (JOHNSON & JOHNSON) 25 December 1973 (1973-12-25)</p> <p>-----</p> | |

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PLI/IB 99/00978

| Patent document cited in search report | Publication date | Patent family member(s) | Publication date |
|---|---------------------|----------------------------|---------------------|
| WO 9625902 A | 29-08-1996 | AU 1217599 A | 15-04-1999 |
| | | AU 706113 B | 10-06-1999 |
| | | AU 4785496 A | 11-09-1996 |
| | | BR 9607429 A | 26-05-1998 |
| | | CA 2213205 A | 29-08-1996 |
| | | CN 1176589 A | 18-03-1998 |
| | | EP 0814736 A | 07-01-1998 |
| | | EP 0901781 A | 17-03-1999 |
| | | US 5827252 A | 27-10-1998 |
| EP 0295694 A | 21-12-1988 | JP 1071740 A | 16-03-1989 |
| | | KR 9602725 B | 26-02-1996 |
| | | US 4857393 A | 15-08-1989 |
| US 4758239 A | 19-07-1988 | NONE | |
| EP 0539604 A | 05-05-1993 | JP 4337342 A | 25-11-1992 |
| | | JP 5009334 A | 19-01-1993 |
| | | JP 5051483 A | 02-03-1993 |
| | | JP 5092507 A | 16-04-1993 |
| | | JP 5093092 A | 16-04-1993 |
| | | DE 69220883 D | 21-08-1997 |
| | | DE 69220883 T | 20-11-1997 |
| | | US 5384187 A | 24-01-1995 |
| | | WO 9220739 A | 26-11-1992 |
| GB 1341605 A | 25-12-1973 | NONE | |